


TrustBox Diode Quickstart Guide



CONTENTS OF THE BOX:

- 1x Trustbox Diode
- 1x 24v PSU Cable and Adapter
- 1x USB-B 2.0 Management Cable
- 2x Networking Cable




1 Unpack



- Remove all components from its packaging

2 Mount on rail




- Mount TrustBox Diode on the DIN rail using the mounting bracket on the back of the device
- Leave sufficient clearance around the device of (2cm) for cooling

3 Plug in power supply



- Connect provided power supply unit into the indicated plug on bottom side

4 Verify status LEDs



- Correct PSU connection is verified when both green (PWR) lights are lit

TrustBox Diode Quickstart Guide



5 Plugin IN (black) port



- Connect desired networking (OT) device
- Possible device list:
 - switch
 - gateway
 - router

6 Plugin OUT (red) port



- Connect desired networking (IT) device
- Possible device list:
 - switch
 - gateway
 - router

7 Verify data transmission



- Correct data transmission is verified when both yellow (ST) lights are flashing
- Successful setup!



TROUBLESHOOTING:

For additional questions visit:

<https://scalys.com/solutions/trustboxdiode/f-a-q/>

Scalys B.V.

A: Amarilstraat 14, 7554TV Hengelo

T: +31 (0)74 2555 712